

TOTO®

Perfection by Design

Manual Urinal Flushometer Valve Exposed – 1.0GPF

To be specified:

Urinal Flush Valve

- Valve Only, 1.0 GPF - TMU1HNC
- Complete Set, 1.0 GPF - TMU1HNC-12(3/4" V.B.)
- Complete Set, 1.0 GPF - TMU1HNC-22(1 1/4" V.B.)

Complete Set Supplied With:

- Vacuum Breaker & Angle Stop Set - VB9CP-12
 - 3/4" Angle Stop - 10077t4
 - 3/4" Vacuum Breaker - 10075t2
 - Spud Nut & Escutcheon - 71051Nt6
 - Sweat Solder Kit - TH559EDVSJ1
- Vacuum Breaker & Angle Stop Set - VB9CP-22
 - 3/4" Angle Stop - 10077t4
 - 1 1/4" Vacuum Breaker - 10075t5
 - Spud Nut & Escutcheon - 71051Nt7
 - Sweat Solder Kit - TH559EDVSJ1

Meets the American Disabilities Act Guidelines and ANSI A117.1 requirements for people with disabilities.



TMU1HNC -12

FLUSHOMETER VALVE

TOTO's superior quality manual flushometer valves incorporate a durable brass body with polished chrome finish, adjustable tailpiece, back-check angle stop with vandal-proof cap, vacuum breaker outlet tube, wall flange, fixture spud escutcheon and spud nut.

SUPERIOR PISTON VALVE TECHNOLOGY

TOTO's piston valve technology is a marked improvement over traditional rubber diaphragm type valves. Not only does the longer piston travel and self-cleaning, stainless steel debris screen reduce common problems such as continuous running and flooding, but the piston itself will not warp or mis-seal, thus significantly reducing repair and maintenance costs.



NEW STANDARD OF PERFORMANCE

A superior and unparalleled engineering design assures a consistently strong flushing action even under a wide range of pressures. The valve is easily adjusted to suit the needs of any manufacturer's fixture.



Manual Urinal Flushometer Valve Exposed – 1.0 GPF

SPECIFICATIONS

Product	TMU1HNC - Valve Only, 1.0 GPF, Right/Left Hand Rough TMU1HNC-12 - Complete Set(3/4" V.B.), 1.0 GPF, Right/Left Hand Rough TMU1HNC-22 - Complete Set(1 1/4" V.B.), 1.0 GPF, Right/Left Hand Rough
Fixture Type	Wash down flush design urinal 1.0 GPF flushometer type
Water supply pipe	3/4" NPT
Water supply pressure	15 psi - 100 psi
Listings	 City of Los Angeles  A.S.S.E. 1037
Warranty	Limited one (1) year warranty on all component parts. Details available upon request.

These dimensions and specifications are subject to change without notice.

SUGGESTED ENGINEERING SPECIFICATION:

TOTO Model No. _____

Manual urinal flushometer valve, piston type with stainless steel, self-cleaning debris screen and precise flushing capability. Low consumption 1.0 GPF model. Polished

chrome exterior, angle stop with back-check and vacuum breaker included.

DIAGRAM:

