## **TOTO**<sub>®</sub>

# UT445UX

### 0.125GPF High-Efficiency Washout Urinal

#### FEATURES

- Full size urinal with concealed integral trap
- Washout flush action with 3/4" top spud inlet
- 0.125 GPF with any TOTO flush valve shown below
- Complete with low profile dome strainer
- Designed for reclaimed water use

#### MODELS

• UT445UX Urinal with 3/4" top spud inlet

#### ADDITIONAL ITEMS

#### EcoPower<sup>®</sup> Flush Valves (0.125 GPF)

Exposed

TEU1UAX12#CP

#### COLORS/FINISHES

• #01 Cotton

#### PRODUCT SPECIFICATION

The wall-mounted, ADA compliant, high-efficiency washout urinal shall be 0.125GPF/0.473LPF when paired with a TOTO 0.125GPF flushometer valve. Urinal specified shall be TOTO Model UT445UX\_\_\_.

Flush valve specified shall be TOTO Model \_\_\_\_\_



#### CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1,
- Certifications: IAPMO(cUPC), State of Massachusetts, City of Los Angeles
- Code compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative Compliance: California AB715, CALGreen Title 24, California Energy Commission Standards
- ADA compliant



#### 0.125GPF High-Efficiency Washout Urinal

#### **SPECIFICATIONS**

Water Use	0.125GPF/0.473LPF	
Flush System	Washout flush action	
Warranty	One Year Limited Warranty	
Material	Vitreous China	
Min. Water Pressure	15 psi (Flowing)	
Height (Urinal Only)	26"	
Width	17-3/4"	
Rim	14-1/4"	
Shipping Weight	UT445UX - 60lbs	
Shipping Dimensions	UT445UX 29" L x 18" W x 16" H	


#### INSTALLATION NOTES

RECLAIMED WATER QUALITY PARAMETERS		
Chloride Ion Concentration	< 600mg/L	
рН	5.8~8.6	
Free Carbonate	< 50mg/L	
Langelier's Index	> -3.00	
Nitrate Ion Concentration	< 60mg/L	
Conductivity	< 250mS/m	
Sulfate Ion Concentration	< 100mg/L	
<b>Residual Chlorine Concentration</b>	< 2mg/L	
Hydrogen Sulfide Gas	None Existance	
Suspended Solids	< 5mg/L	

Ultra-low high efficiency urinals require a system with a minimum 2% slope. Maximum drainage capacity rated at 6.6 gal/min (25 L/min). Adjust angle stop accordingly to prevent overflow. Confirm with local codes and standards for floor drain requirement.

TOTO Reclaimed Water flush valves are designed to perform best when used with TOTO Reclaimed Water urinals/toilets and components. Although TOTO Reclaimed Water products may be used in combination with other reclaimed water product brands, optimal performance might be impaired and attempted use with any non-compliant reclaimed water product(s) could result in corrosion, leakage or void the warranty.

#### DIMENSIONS



TOTO<sub>®</sub>