

## Modern Series Aero Rain Shower

### FEATURES

- Air injected and pulsating AeroJet+ Technology
- 2.5 gpm (9.5 lpm) maximum flow rate
- 12" diameter spray face
- Rubber nozzles to prevent lime scale build up

### COLORS/FINISHES

- #CP Polished Chrome
- #BN Brushed Nickel
- #PN Polished Nickel



### CODES/STANDARDS

- Meets or exceeds ASME A112.18.1/CSA B125.1
- Certifications: IAPMO(cUPC), State of Massachusetts and others
- Code Compliance: UPC, IPC, NSPC, NPC Canada, and others



### PRODUCT SPECIFICATION

The show shall have air injected and pulsating Aero-Jet+ technology. Product shall have 2.5 gpm (9.5 lpm) max flow rate. Product shall have 12" diameter spray face. Product shall have rubber nozzles to prevent lime scale build up. Product shall be TOTO Model TS111B12#\_\_\_\_\_.

Please note the following required components are sold separately:



TS110MW16  
Shower Arm Wall  
Mount



TS110MC6  
Shower Arm Ceiling  
Mount

# TS111B12

## Modern Series Aero Rain Shower

### SPECIFICATIONS



- Warranty: Lifetime Limited Warranty (Residential Use)  
One Year (Commercial Use)
- Material: Brass
- Shipping Weight: 7.4 lbs.
- Shipping Dimensions: 13-1/8" x 14-1/8" x 4-1/4"
- Maximum Flow Rate: 2.5 gpm (9.5 lpm)

### INSTALLATION NOTES


#### Required Components:

- TS110MW16\* (Wall Mount Shower Arm)
- TS110MC6\* (Ceiling Mount Shower Arm)

\*These components are compatible with the following TOTO rain shower products only:  
TS111B8, TS111BL8, TS111B12, TS111BL12,  
TS112B8, TS112BL8, TS112B12, TS112BL12



Shown with  
TS110MW16



Shown with  
TS110MC6