

Standard-R Touchless Faucet

FEATURES

- The choice of self-generating hydropowered ECOPOWER® system or AC system
- IoT-ready product (ECOPOWER models only) – requires communication card sold separately for IoT functionality
- Micro-sensor positioned underneath the spout head provides accurate hand detection and ensures smooth, consistent water distribution
- Vandal resistant nozzle
- Laminar flow
- Durable chrome plated spout body
- Kit includes spout body, controller box, and mounting hardware (supply lines not included)
- Equipped with 1.0 gpm flow control. 0.18 gpc, 10 sec on-demand flow
- IoT-enabled options available to remotely monitor usage rates, water consumption, fixture performance and streamline operations in real time with instant alerts

OPTIONAL ACCESSORIES

- **THP3158#CP** - 4" Cover Plate
- **THP3159#CP** - 8" Cover Plate
- **THP3237** - Swivel Coupling

COLORS/FINISHES

- #CP Polished Chrome

PRODUCT SPECIFICATION

TOTO Model # _____ Choice of self-generating hydro-powered ECOPOWER system or AC system. The faucet shall have maximum of 10 seconds on-demand flow (0.18 gpc). The faucet shall have self-adjusting sensor. Product equipped with 1.0 gpm flow regulator.



ECOPOWER OR AC SYSTEM

CODES/STANDARDS

- Operates below federally mandated consumption limit of 0.25 gpc
- Complies to California Green Building Code, CALGreen max flow of 0.20 gpc
- Meets or exceeds ASME A112.18.1/CSA B125.1, and NSF 372
- Meets or exceeds UL 1951, CSA C22.2 No.14 and 68 (AC systems only)
- Certifications: IAPMO(cUPC), California Energy Commission (CEC), State of Massachusetts, and others
- Complies with City of Los Angeles Water Efficiency Ordinance
- ADA compliant
- Complies with Federal and State statutes as low-lead (contains a weighted average of 0.25% lead or less)
- Complies with CA Prop 65 warning requirements
- FCC compliant to Part 15 (for IoT only)

*For codes and standards of mixing valves TLM10 and TLE05701U, please refer to corresponding product spec sheet



ECOPOWER MODELS

Kit Options	Component Breakdown				
	Spout	ECOPOWER Controller	Mixing valve	Thermo Mixing Valve	IoT Card
T28S11Ei#\$\$	TLE28003U1#\$\$	TLE03503U1i			*
T28S11EiM#\$\$	TLE28003U1#\$\$	TLE03503U1i	TLM10		*
T28S11EiT#\$\$	TLE28003U1#\$\$	TLE03503U1i		TLE05701U	*
T28S11Ei4#\$\$	TLE28003U1#\$\$	TLE03503U1i			THP3566

*Requires communication card (sold separately) for IoT functionality

AC MODELS (Not IoT Compatible)

Kit Options	Component Breakdown			
	Spout	AC Controller	Mixing valve	Thermo Mixing Valve
T28S11A#\$\$	TLE28003U1#\$\$	TLE01503U		
T28S11AM#\$\$	TLE28003U1#\$\$	TLE01503U	TLM10	
T28S11AT#\$\$	TLE28003U1#\$\$	TLE01503U		TLE05701U

T28S11i Series

Standard-R Touchless Faucet

SPECIFICATIONS


Type	ECOPOWER	AC
Power Supply	Hydropower Generation (self-powering power supply)	AC 120V
IoT Capability	IoT-Enabled	
Sensor Detection Range	5-1/8" ~ 7-7/8" (130 ~ 200 mm) Sensor is self-adjusting	
Water Supply Pressure	Min (Dynamic/Flowing) Pressure: 15 psi (100 kPa) Max (Static) Pressure: 80 psi (551 kPa)	
Water Supply	G 1/2" (1/2" NPSM compatible)	
Inlet Temperate Range	39-110°F (4-43°C)	
Ambient Temperate	32-104°F (0-40°C)	
Humidity	Max. 90% RH	
Flow Rate	0.18 gpc (0.68 Lpc)** - max 10 second On Demand*** (0.18 gpc = 1.0 gpm x 10/60 sec) Equipped with 1.0 gpm flow control	
Warranty	Three years	

**Gallons per cycle (gpc) is the amount of water discharged per usage cycle.

*** On-demand refers to the way in which the water is dispensed (i.e.; water is only dispensed when the sensor is activated by the user as needed).


DIMENSIONS

Standard-R Touchless Faucet




- Mounting deck thickness: 1/4" (5 mm) - 2" (50 mm)
- Spout hole: Ø1-1/4" (Ø32 mm) - Ø1-3/8" (Ø35 mm)


ECOPOWER Controller



Available Mixing Valves




Hot/Cold Mixing Tee (TLM10)



Thermostatic Mixing Valve (TLE05701U)

AC Controller



These dimensions and specifications are subject to change without notice

TOTO®