

### FEATURES

- Maximum flow rate of 2.5 gpm (9.5 lpm)
- Rubber nozzles to prevent limescale build up
- 5" diameter spray face
- Single spray showerhead
- Includes shower arm and escutcheon
- 1/2" NPT connection

### COLORS/FINISHES

- #CP Polished Chrome
- #BN Brushed Nickel
- #PN Polished Nickel



### CODES/STANDARDS

- Meets or exceeds ASME A112.18.1/CSA B125.1
- Certifications: IAPMO(cUPC), State of Massachusetts and others
- Code Compliance: UPC, IPC, NSPC, NPC Canada, and others



### PRODUCT SPECIFICATION

The showerhead shall have a maximum flow rate of 2.5 gpm (9.5 lpm). Showerhead shall have rubber nozzles to prevent limescale build up. Product shall have a 5" diameter spray face. Product shall have a single spray. Product shall include shower arm and escutcheon. Product shall have a 1/2" NPT connection. Product shall be TOTO Model TS970AR#\_\_\_\_\_.

## SPECIFICATIONS

- Warranty Lifetime Limited Warranty  
(Residential Use)  
One Year (Oil Rubbed Bronze)  
One Year (Commercial Use)
- Material Brass
- Shipping Weight 11.0 lbs.
- Shipping Dimensions 14" L x 8-3/4" W x 5-1/2" H
- Maximum Flow Rate 2.5 gpm (9.5 lpm)

