TL170DDA12

Kiwami[®] Renesse[®] Widespread Lavatory Faucet without Pop-up Drain

FEATURES

- WaterSense certified low-flow 1.2 gpm (4.5 lpm) faucet
- Solid brass construction
- Ceramic disk valve cartridge
- Accommodates 8"-16" spread
- Without pop-up drain



COLORS/FINISHES

#CP Polished Chrome

CODES/STANDARDS

- Complies with federal and state lead-free legislation
- Meets or exceeds ASME A112.18.1/CSA B125.1, NSF 61-9, NSF 372
- Certifications: IAPMO(cUPC), EPA WaterSense, California Energy Commission (CEC), State of Massachusetts and others
- Code Compliance: UPC, IPC, NSPC, NPC Canada, California Green Building Code, City of Los Angeles Water Efficiency Ordinance, City of New York and others
- Complies with CA Prop 65 warning requirements





PRODUCT SPECIFICATION

The widespread lavatory faucet shall have a maximum flow rate of 1.2 gpm (4.5 lpm). Product shall have a solid brass construction. Product shall have a ceramic disk valve cartridge. Product shall accommodate 8"-16" spread. Product shall be TOTO Model TL170DDA12#CP.

Kiwami[®] Renesse[®] Single-handle Lavatory Faucet without Pop-up Drain

SPECIFICATIONS

Warranty Lifetime Limited Warranty

(Residential Use)

One Year (Commercial Use)

Material Brass

Maximum Flow Rate 1.2 gpm (4.5 lpm)

Shipping Weight 11.0 lbs.

• Shipping Dimensions 20-1/2"L x 11"W x

3-1/2"H





