

## Drake® Transitional Close Coupled Toilet, 1.28 and 0.8 GPF

### FEATURES

- DYNAMAX TORNADO FLUSH® utilizes 360° cleaning power to reach every part of the bowl
- High-efficiency dual flush 1.28 & 0.8 GPF (4.8 & 3.0 LPF)
- CEFIONTECT® ceramic glaze prevents debris and mold from sticking to ceramic surfaces
- Design of the bowl reduces water flow resistance resulting in a quieter flushing sound
- Elongated front bowl, less seat
- Universal Height
- Chrome plated trip lever
- 12" Rough-in
- Semi-concealed trapway

### MODELS

- **CST748CEMFG** (#01, #03, #11, #12)  
With CEFIONTECT ceramic glaze
- **CST748CEMF** (#51)  
Without CEFIONTECT ceramic glaze

### COMPONENTS

- **CT746CUF(G)**  
Elongated bowl with CEFIONTECT
- **ST748EMA**  
Tank and cover only

### COLORS/FINISHES

- |  |   |
|--|---|
| <ul style="list-style-type: none"> <li>• #01 Cotton</li> <li>• #12 Sedona Beige</li> </ul> | <p><b>Made to Order</b></p> <ul style="list-style-type: none"> <li>• #03 Bone</li> <li>• #11 Colonial White</li> <li>• #51 Ebony</li> </ul> |
|--|---|



- **DYNAMAX TORNADO FLUSH**
- **Universal Height**
- **CEFIONTECT**
- **WATER SAVING**

### PRODUCT SPECIFICATION

The two-piece high-efficiency DYNAMAX TORNADO FLUSH toilet shall be dual flush 1.28 GPF/0.8 GPF. Toilet shall be 12" rough-in. Toilet shall have optional CEFIONTECT ceramic glaze and be at Universal Height. Toilet shall have elongated front bowl and chrome plated trip lever. Toilet shall be TOTO Model CST748CEMFG.

### CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1, ASME A112.19.14
- Certifications: IAPMO(cUPC®), EPA WaterSense, State of Massachusetts, and others
- Code Compliance: UPC, IPC, NSPC, NPC Canada, and others
- Complies with CA AB715, CA Green Building Code, Los Angeles Water Efficiency Ordinance and others
- ADA compliant (when installed with trip lever located on the approach side)
- Complies with CA Prop 65 warning requirements



# CST748CEMFG


## Drake® Transitional Close Coupled Toilet 1.28 and 0.8 GPF INSTALLATION NOTES

### SPECIFICATIONS

<b>Water Use</b>	1.28 & 0.8 GPF (4.8 & 3.0 LPF)
<b>Flush System</b>	DYNAMAX TORNADO FLUSH®
<b>Min. Water Pressure</b>	8 psi (Static)
<b>Water Surface</b>	5-5/8" x 4-1/8"
<b>Trap Diameter</b>	2-1/2"
<b>Rough-in</b>	12"
<b>Trap Seal</b>	2-1/8"
<b>Warranty</b>	One Year Limited Warranty
<b>Material</b>	Vitreous China
<b>Shipping Weight</b>	CT746CUF(G) 66 lbs. ST748EMA 33.1 lbs.
<b>Shipping Dimensions</b>	CT746CUF(G) 28-1/4" L x 17-1/4" W1 x 10-3/4" W2 x 17-1/4" H ST748EMA 19-7/8" L x 9-3/8" W x 15-5/8" H


### Back-to-Back Toilet Installations:

TOTO recommends the use of a nationally listed, double sanitary tee-wye only, in vertical waste stacks, in accordance with the stipulations noted in the majority of nationally recognized plumbing codes.



To maintain adequate wall gap between the back of the tank and wall, mount the floor flange at a nominal 12" rough-in distance.

### DIMENSIONS



**TOTO®**

Fixture Dimensions shown are nominal. These dimensions and specifications are subject to change without notice.

Ph: (888) 295-8134 | Fax: (800) 699-4889 | www.totousa.com | © TOTO USA

# SS-01636 v.01