

FEATURES

- Wireless Communication
- Connects seamlessly with Georgia-Pacific's (GP) KOLO™ Smart Monitoring System and through an API to facilities monitoring platforms
- Service agreement with GP required to enable IoT or Smart Features
- Auto soap dispenser's operation is independent of its IoT capability
- Some of the IoT-enabled Smart Features include: failure detection, usage and soap consumption.
- Sensor operated foaming soap dispenser
- Self-adjusting sensor spout with base unit, mounting hardware and supply lines
- Chrome plated
- Single-hole mount
- TOTO Soap required
- Refillable tank system
- ADA compliant
- *Additional product benefits and features are available by contacting TOTO IoT/Smart Products Experts (or Division) or a TOTO sales representative*



COLORS/FINISHES

- #CP Polished Chrome

OPTIONAL ACCESSORY

- THP3140#CP
Escutcheon 1-1/8" ~ 1-1/2" (28mm~38mm)
- THP3374
Mount Bracket

MODELS

- TES201AAi2#CP (1 Spout)
TLK03001G#CP (Spout x 1 pc)
TLK01101Ui2 (Controller for 1 Spout & Reservoir)
- TES202AAi2#CP (2 Spouts)
TLK03001G#CP (Spout x 2 pcs)
TLK01102Ui2 (Controller for 2 Spouts & Reservoir)
- TES203AAi2#CP (3 Spouts)
TLK03001G#CP (Spout x 3 pcs)
TLK01103Ui2 (Controller for 3 Spouts & Reservoir)

COMPONENT BREAKDOWN

Soap Dispenser Specification Details

Step 1: Choose quantity of spouts desired

Step 2: Select kit or by individual component quantities

KIT OPTIONS	
Kit Model #	Spout Installation
TES201AAi2#CP	1
TES202AAi2#CP	2
TES203AAi2#CP	3



COMPONENTS			
SPOUT		CONTROLLER & RESERVOIR	
Model #	Spout Qty	Model #	Component Qty
TLK03001G#CP	1	TLK01101Ui2	1 (For 1 Spout)
TLK03001G#CP	2	TLK01102Ui2	1 (For 2 Spouts)
TLK03001G#CP	3	TLK01103Ui2	1 (For 3 Spouts)

PRODUCT SPECIFICATION

TOTO® Model No. _____

Product shall be automatic infrared sensor activated. Product shall have automatic sensor adjustment upon installation. Soap dispenser and controller w/ reservoir will be sold separately. Product shall have a controller pump with 0.8 gallon (3L) reservoir.

CODES/STANDARDS

- Meets and exceeds UL1951, CSA C22.2 #68
- FCC compliant to Part 15
- Certifications: UL
- Code Compliance: FCC, NEC, CEC
- ADA Compliant
- Complies with CA Prop 65 warning requirements



TES20(1/2/3)AAi2 Series

IoT-Enabled Auto Soap Dispenser

SPECIFICATIONS

Power Supply	AC 120V
Wattage	(TLK01101Ui2) 4W (TLK01102Ui2) 6.5W (TLK01103Ui2) 9W
Sensor Detection Range	5-1/8" ~ 7-7/8" (130~200mm) Sensor is self-adjusting
Ambient Temperature	34-104°F(1-40°C)
Humidity	Max. 90% RH
Power Cord Length	55" (1.4 m)
Soap Output Volume	0.04 oz (factory setting)
Tank Capacity	Approximately 0.8 gal (3L)
Warranty	*Three Year Warranty

*Failure to use TOTO soap will void warranty

INSTALLATION NOTES

- Spout Mounting Hole $\phi 1" \sim \phi 1\text{-}1/8"$ ($\phi 25 \sim \phi 28$ mm)
- Deck Thickness 1/4" ~ 1-1/8" (5 ~ 30 mm)


A minimum of 13/16" (20mm) clearance on the right side of the controller is required for IoT daughter card installation. Please refer to the diagram below.

TOTO SOAP *(Sold Separately)*

SKU No.	Quantity	Packaging	Notes
TSFG1	4 gal.	Package of 4, 1 gal. each	Antimicrobial Soap (Fresh)
TSFG55	55 gal.	Package of 1, 55 gal. each	Antimicrobial Soap (Fresh)
TSFB1-GS	4 gal.	Package of 4, 1 gal. each	TOTO Foam Soap Green Seal™ (Lilac)



DIMENSIONS



TOTO

These dimensions and specifications are subject to change without notice