TOTO

MW6043046CEFG(A)

UltraMax® II / WASHLET®+ S500e One-Piece Toilet - 1.28 GPF

FEATURES

- Concealed supply connection for seamless installation
- TORNADO FLUSH® system, high-efficiency (1.28GPF/4.8LPF)
- CEFIONTECT® glaze prevents debris from sticking to ceramic surfaces for easy cleaning
- Universal Height
- Decorative one-piece design with elongated bowl
- Chrome trip lever
- 12" Rough-in, supply line sold separately
- See Spec sheet SW3046AT40 for WASHLET features

MODELS & COMPONENTS

MW6043046CEFGA#01

With CEFIONTECT ceramic glaze, WASHLET+ S500e and Auto Flush

- CST604CEFGAT40

Elongated bowl with CEFIONTECT

- SW3046AT40

WASHLET+ S500e

- THU767

Auto Flush Kit

MW6043046CEFG#01

Same as MW6043046CEFGA without Auto Flush

- CST604CEFGAT40

Elongated bowl with CEFIONTECT

- SW3046AT40

WASHLET+ S500e

COLORS/FINISHES

 Standard #01 Cotton

PRODUCT SPECIFICATION

The one-piece high-efficiency TORNADO FLUSH toilet shall be 1.28GPF/4.8LPF. Universal Height Toilet with CEFIONTECT glaze finish. Toilet shall have high-profile tank, elongated front bowl and chrome trip lever. Toilet shall be TOTO Model MW6043046CEFG #01.

See TOTO Specification sheet SW3046AT40 for details on required WASHLET.











CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1
- Certifications: IAPMO(cUPC), EPA WaterSense, State of Massachusetts, City of Los Angeles, and others
- Code compliance: UPC, IPC, NSPC, NPC Canada,
- Legislative Compliance: California AB715, California Green Building Code, City of Los Angeles Water Efficiency Ordinance
- ADA compliant (when installed with trip lever located on the approach side)
- Complies with CA Prop 65 warning requirements







UltraMax® II / WASHLET®+ S500e One-Piece Toilet - 1.28 GPF

SPECIFICATIONS

Water Use
 Flush System
 Min. Water Pressure
 Water Surface
 Trap Diameter
 1.28 GPF/4.8LPF
TORNADO FLUSH®
 8 psi (static)
 6-3/4" x 8-5/8"
 2-1/8"

Trap Diameter 2-1/8"
 Rough-in 12"
 Trap Seal 2-1/8"

Warranty
 One Year Limited Warranty

Material Vitreous china

• Shipping Weight CST604CEFGAT40: 99lbs. SW3046AT40: 15.6lbs.

• Shipping Dimensions CST604CEFGAT40

32"L x 20"W x

17-3/4"H¹ x 28-3/4"H²

SW3046AT40


23-3/4"L X 17"W X 9-1/2"H

See Spec sheet SW3046AT40 for WASHLET details

INSTALLATION NOTES

Back-to-Back Toilet Installations:

TOTO recommends the use of a nationally listed, double sanitary tee-wye only, in vertical waste stacks, in accordance with the stipulations noted in the majority of nationally recognized plumbing codes.



Install this product according to the installation guide.

Will comply with ADA when installed per Section 604 Water Closetsand Toilet Compartments of the ADA 2010 Accessible Design Standard with seat height between 17" to 19", trip lever on approach side and flush actuation force of less than 5lbs.

Will comply with CSA B651 when installed per Clause 6.2.6 Toilets of the CSA 2012 Accessible Design Standard with seat height between 17" to 19", trip lever on approach side and flush actuation force of less than 5lbs.

