

MW4424736CEFG(A)

FEATURES

- Concealed supply connection for seamless installation
- High-efficiency TORNADO FLUSH® system 1.28 GPF (4.8 LPF)
- CEFIONTECT_® ceramic glaze minimizes waste from sticking to porous ceramic surfaces
- Completely skirted design for a sleek and understated look that's easier to clean
- Universal Height
- Chrome plated trip lever
- 12" Rough-in
- Elongated front bowl and WASHLET+ S7A and tank set
- EWATER+® auto-cleans wand and bowl after every use
- PREMIST® automatically mists the bowl before each use
- Multifunction pearl white block-style remote control
- Auto open/close lid
- Night light
- Auto flush available as upgrade

MODELS

- MW4424736CEFGA (#01)
 With CEFIONTECT ceramic glaze, WASHLET+ S7A with contemporary design and Auto Flush
 - CT442CUFGT40 Elongated bowl with CEFIONTECT
 - **ST442EA** Tank and cover only
 - SW4736AT40
 - WASHLET+ S7A
 - THU857 Auto Flush Kit
 - 9AU321-A WASHLET Adaptor
- MW4424736CEFG (#01) Same as MW4424736CEFG without Auto Flush

OPTIONAL COMPONENTS

- TSU10W.14 14" Unifit Rough-In
- THU750(#01, #BN, # PN)
 Trip Lever (Cotton, Brushed Nickel, Polished Nickel)

COLORS/FINISHES

• #01 Cotton

Nexus® WASHLET®+ S7A Two-Piece Toilet - 1.28 GPF



UNIVERSAL HEIGHT

PRODUCT SPECIFICATION

The two-piece high-efficiency TORNADO FLUSH system toilet shall be 1.28 GPF (4.8 LPF). Toilet shall be 12" Unifit rough-in. Toilet shall have CEFIONTECT ceramic glaze and be at Universal Height. Toilet shall have elongated front bowl and Polished Chrome trip lever. Toilet shall be TOTO Model MW4424736CEFG___#01.

See SW4736AT40 Specification Sheet for details on included WASHLET.

CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1
- Certifications: IAPMO (cUPC_®), EPA WaterSense_®, State of Massachusetts, City of Los Angeles, and others
- Code compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative Compliance: California AB715, California Green Building Code, City of Los Angeles Water Efficiency Ordinance, and others
- ADA compliant for residential use with autoflush feature model, or with trip lever located on the approach side
- Complies with CA Prop 65 warning requirements



Nexus® WASHLET®+ S7A Two-Piece Toilet - 1.28 GPF

SPECIFICATIONS


Water Use	1.28 GPF (4.8 LPF)
Flush System	TORNADO FLUSH®
Min. Water Pressure	8 psi (Flowing)
Water Surface	6-5/8" x 9-1/8"
Trap Diameter	2-1/8"
Rough-in	12" (14" option available)
Trap Seal	2-1/8"
Warranty	One Year Limited Warranty
Material	Vitreous China
Shipping Weight	CT442CUF(G)T40: 87 lbs ST442EA: 25 lbs SW4736AT40: 15 lbs
Shipping Dimensions	CT442CUF(G)T40 29-3/4"L x 18-1/4"W x 18-3/4"H ST442EA 17-1/4"L x 7-7/8"W x 17-1/2"H SW4736AT40 23-3/8" L x 17-5/8" W x 6-1/4" H

See SW4736AT40 Specification Sheet for details on included WASHLET.

INSTALLATION NOTES


Back-to-Back Toilet Installations:

TOTO recommends the use of a nationally listed, double sanitary tee-wye only, in vertical waste stacks, in accordance with the stipulations noted in the majority of nationally recognized plumbing codes.



To maintain adequate wall gap between the back of the tank and wall, mount the floor flange at a nominal 12" rough-in distance.

DIMENSIONS



Ph: (888) 295-8134 | Fax: (800) 699-4889 | www.totousa.com | © TOTO USA